

SDL Series

Outline Drawings



To work with



SVH



SMH

Specifications

Model	Applicable Dryer	Applicable Loader	Applicable Hopper Receive	Conveying Capacity (kg/hr)	Hopper Capacity (L)	Dimension (mm) H x W x D	Weight (kg)
SDL-25	SHD-25	SAL-700G or 800G	1 x SVH-6L	300	6	1620x1000x640	95
		SAL-900G	1 x SVH-6L 1 x SMH-6L	450	2 x 6		
SDL-50	SHD-50	SAL-700G or 800G	1 x SVH-6L	300	6	1750x1000x640	110
		SAL-900G	1 x SVH-6L 1 x SMH-6L	450	2 x 6		
SDL-75	SHD-75	SAL-700G or 800G	1 x SVH-6L	300	6	1850x1000x640	115
		SAL-900G	1 x SVH-6L 1 x SMH-6L	450	2 x 6		
SDL-100	SHD-100	SAL-700G or 800G	1 x SVH-6L	300	6	1950x1080x710	155
		SAL-900G	1 x SVH-6L 1 x SMH-6L	450	2 x 6		
SDL-150	SHD-150	SAL-700G or 800G	1 x SVH-6L	300	6	2200x1080x710	160
		SAL-900G	1 x SVH-6L 1 x SMH-6L	450	2 x 6		
SDL-200	SHD-200	SAL-800G	1 x SVH-6L	300	6	2385x1140x840	210
		SAL-900G	1 x SVH-6L 1 x SMH-6L	450	2 x 6		
SDL-300	SHD-300	SAL-800G	1 x SVH-6L	300	6	2690x1140x840	220
		SAL-900G	1 x SVH-6L 1 x SMH-6L	450	2 x 6		
SDL-400	SHD-400	SAL-800G2	1 x SVH-12L	400	12	2800x1240x1020	285
		SAL-900G2	1 x SVH-12L 1 x SMH-12L	700	2 x 12		

Notes: 1) Install 24hr timer, add "T" at the end of the model code.

2) Magnetic bases are applied to SHD-300 and models below, add "M" at the end of the model code.

3) When applying double insulated layer, add "I" at the end of the model code.

4) Power: 3Φ, 230/400/460/575VAC, 50/60Hz.

We reserve the right to change specifications without prior notice.