




Options



Touch Screen
(LCD with PLC Control)



Dew-point Monitor
(Installed on the machine)



SCD-OP High Efficiency
Particulate Absorbing Filter

Outline Drawings



Specifications

Model	Regen. Heater (kW)	Regen. Blower (kW, 50/60Hz)	Drying Heater (kW)	Drying Blower (kW, 50/60Hz)	Dry Air Volume (m ³ /hr, 50/60Hz)	Insulated Hopper (L)	Dimension (mm) H X W X D	Weight (kg)
20U / 30H	3	0.2/0.2	3	0.2/0.2	30/35	20	1240 × 875 × 810	110
40U / 30H	3	0.2/0.2	3	0.2/0.2	30/35	40	1300 × 930 × 810	190
40U / 50H	3	0.2/0.2	3.9	0.4/0.5	50/60	40	1300 × 930 × 810	190
80U / 50H	3	0.2/0.2	3.9	0.4/0.5	50/60	80	1410 × 1030 × 810	210
120U / 80H	3	0.2/0.2	6	0.75/0.9	80/95	120	1780 × 1220 × 855	250
160U / 80H	3	0.2/0.2	6	0.75/0.9	80/95	160	1740 × 1220 × 855	255
160U / 120H	3	0.2/0.2	6	0.75/0.9	120/130	160	1740 × 1220 × 855	265
230U / 120H	3	0.2/0.2	6	0.75/0.9	120/130	230	2010 × 1220 × 855	295
230U / 150H	4	0.4/0.5	12	1.5/1.8	150/170	230	2150 × 1450 × 1050	375
300U / 150H	4	0.4/0.5	12	1.5/1.8	150/170	300	2040 × 1450 × 1050	410
300U / 200H	4	0.4/0.5	12	1.5/1.8	200/220	300	2040 × 1450 × 1050	420
450U / 200H	4	0.4/0.5	12	1.5/1.8	200/220	450	2440 × 1450 × 1050	550
450U / 300H	7.2	0.75/0.9	15	2.4/3	300/340	450	2480 × 1490 × 1255	580
600U / 300H	7.2	0.75/0.9	15	2.4/3	300/340	600	2380 × 1745 × 1255	615
600U / 400H	7.2	0.75/0.9	18	3.75/4.5	400/450	600	2380 × 1745 × 1255	620
750U / 400H	7.2	0.75/0.9	18	3.75/4.5	400/450	750	2610 × 1745 × 1255	650
900U / 700H	10	1.5/1.8	24	5.5/6.3	700/780	900	2640 × 2140 × 1380	830
1200U / 700H	10	1.5/1.8	24	5.5/6.3	700/780	1200	3070 × 2140 × 1380	870

Notes: Power: 3Φ, 230/400/460/575VAC, 50/60Hz.

We reserve the right to change specifications without prior notice.