





# SCR Series

## Outline Drawings



SCR-160U



SCR-450U and Models Above

## Specifications

Model	SCR-160U	SCR-450U	SCR-900U	SCR-1600U	SCR-2500U
Heater Power (kW)	12	24	48	96	128
Blower Power (kW, 50/60Hz)	0.55	2.2	3	7.5	15
Blending Motor Power (kW, 50/60Hz)	0.25	0.55	1.5	1.5	4
Max. Throughput (kg/h)	50	150	300	500	750
Hopper Capacity (L)	160	450	900	1600	2500
H (mm)	2380	3850	4450	5350	5670
H1 (mm)	280	720	1040	860	1270
H2 (mm)	380	1060	1185	1260	1270
W (mm)	1040	2370	2890	3570	4050
W1 (mm)	1140	1440	1930	2190	2350
W2 (mm)	---	800	800	800	800
ØA (inch)	3	5	6	8	8
ØB (inch)	4	4	5	5	5
Weight (kg)	235	500	865	2290	2790

Notes: 1) Above maximum processing capacity is based on uncrystallized PET material of 0.85kg/L in density and 3-5mm in diameter.  
2) Power: 3Φ, 230 / 400 / 460 / 575VAC, 50 / 60Hz.

We reserve the right to change specifications without prior notice.