

# SAL-U Series

## ■ Specifications

Model	SAL-1U	SAL-3U	SAL-6U	SAL-12U	SAL-1.5U-E	SAL-3U-E	SAL-6U-E	SAL-12U-E	SAL-3U-3	SAL-6U-3
Motor Type	Carbon brush								Inductive	
Motor Power (kW, 50/60Hz)	0.46/0.55	1.15/1.32	1.15/1.32	1.15/1.32	1.15/1.32	1.15/1.32	1.15/1.32	1.151.32	0.37/0.42	0.75/0.85
Conveying Pipe Dia. (inch)	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5
Conveying Capacity (kg/hr)	30	200	300	400	150	200	300	400	200	300
Hopper Capacity (L)	1	3	6	12	1.5	3	6	12	3	6
Power Supply	1Φ, 115/230VAC, 50/60Hz								3Φ, 230/400/460/575VAC, 50/60Hz	
Auto-cleaning Function	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Air accumulator	-	-	Optional	Optional	-	-	Optional	Optional	-	-
Dimension										
H (mm)	525	555	645	745	670	740	800	935	610	700
W (mm)	270	305	340	340	260	305	340	340	340	380
D (mm)	325	370	410	410	325	370	410	410	475	540
Weight (kg)	10	11	12	14	11	13	16	18	18	33

Notes: 1) For polished hopper inside ones, add "P" at the end of model code.

- 2) Test condition of conveying capacity: plastic material of bulk density 0.65kg/L, dia. 3~5 mm, vertical conveying height: 4m, horizontal conveying distance: 1m.

- 3) Compressed air supply: 4~6kgf/cm<sup>2</sup>.

We reserve the right to change specifications without prior notice.